

Reading carrying capacity tables for parts handlers

The carrying capacity table gives dynamic allowable load W_o by stroke and rotating speeds.

This table was calculated based on a parts handler that has been mounted and lubricated according to specifications and is being operated under normal condition. Adverse operating conditions and poor maintenance can effect the transmission capacities and life of the parts handler.

Note, when selecting models it is important that the torque transmission capacity table be read correctly in order to make the proper selection. Always make sure to read and understand the following explanations.

Dynamic allowable load and rotating speeds

The dynamic allowable load given in the carrying capacity table will vary according to the stroke. Index period, and rotating speed. The dynamic allowable load may also vary by the mounting position due to the internal load of the parts handler. The allowable rotating speed varies according to the direction of the stroke. Therefore, always check the values according to actual operating conditions.

Stroke I ST _I (mm)	Minimum Index Period θ_1 (deg)	Dynamic Allowable Load W_o (N)							
		Input Shaft Speed N(rpm)							
		10	20	30	40	50	60	70	80
5	30	46.0	37.2	32.3	28.4	27.4	24.5	24.5	23.5
10	41	37.2	28.4	24.5	23.5	22.5	20.5	19.6	19.6
15	48	32.3	25.4	22.5	19.6	18.6	18.6	16.6	16.6
20	52	28.4	23.5	19.6	18.6	16.6	15.6	15.6	14.7
25	56	25.4	22.5	18.6	16.6	15.6	14.7	14.7	12.7
30	60	24.5	19.6	16.6	15.6	15.6	14.7	12.7	11.7

Index periods

Two or more index periods are given for each stroke range. The smallest index period is the minimum index period for that amount of stroke. Cams cannot be manufactured for index periods below this minimum value.

When designing the timing, try to make the index period as large as possible.

Cam curves

The output displacement of the parts handler is produced by a modified sine curve(MS curve). If your application requires synchronized operation at equivalent speeds or special displacement specifications, please consult Sankyo.

8GY

Carrying capacity table of stroke I

Table 8GY-1

Stroke I ST _I (mm)	Minimum Index Period θ_1 (deg)	Dynamic Allowable Load W_o (N)								Camshaft Frictional Torque Tx (N-m)
		Input Shaft Speed N(rpm)								
		10	20	30	40	50	60	70	80	
10	26	110.7	95.1	78.4	75.5	69.6	65.7	61.7	53.9	(8.82)
20	36	87.2	75.5	68.6	64.7	59.8	56.8	54.9	47.0	
30	41	76.4	65.7	61.7	59.8	57.8	55.9	53.9	44.1	
40	45	69.6	61.7	59.8	54.9	51.9	48.0	44.1	29.4	
50	47	64.7	57.8	55.9	51.0	49.0	38.2	34.3	26.5	
60	49	60.8	53.9	52.9	48.0	45.1	31.4	27.4	20.6	
65	54	58.8	52.9	48.0	46.1	44.1	37.2	33.3	24.5	

Carrying capacity table of stroke II

Table 8GY-2

Stroke II ST _{II} (mm)	Minimum Index Period θ_{II} (deg)	Static Allowable Load W _s (N)	Dynamic Allowable Load W_o (N)								Camshaft Frictional Torque Tx (N-m)
			Input Shaft Speed N(rpm)								
			10	20	30	40	50	60	70	80	
10	17	140.1	110.7	95.1	78.4	69.6	62.7	56.8	46.1	30.4	(8.82)
20	23	135.4	87.2	75.5	68.6	59.8	53.9	48.0	34.3	24.5	
30	28	131.7	76.4	65.7	61.7	56.8	51.0	45.1	32.3	22.5	
40	32	127.0	69.6	61.7	59.8	53.9	48.0	42.1	29.4	19.6	
50	35	124.5	64.7	57.8	55.9	49.0	43.1	38.2	26.5	16.7	
60	37	121.0	60.8	53.9	52.9	43.1	37.2	32.3	21.6	12.7	
70	39	118.6	57.8	51.0	49.0	39.2	33.3	28.4	18.6	10.8	
80	41	115.1	54.9	49.0	48.0	36.3	31.4	25.5	15.7	7.8	
90	43	113.9	52.9	47.0	43.1	34.3	28.4	23.5	14.7	7.8	
100	45	110.4	51.0	45.1	41.2	32.3	27.4	21.6	13.7	7.8	
110	47	106.8	49.0	44.1	39.2	30.4	25.5	20.6	11.8	6.9	
120	50	105.7	48.0	43.1	40.2	30.4	23.5	15.7	9.8	7.8	
130	55	103.3	47.0	42.1	40.2	29.4	19.6	14.7	11.8	8.8	
140	73	100.9	45.1	42.1	39.2	35.3	22.5	16.7	14.7	12.7	
150	80	98.6	44.1	41.2	38.2	35.3	26.5	18.6	16.7	15.7	
160	87	95.6	43.1	40.2	37.2	34.3	29.4	22.5	19.6	17.6	
170	92	92.7	43.1	39.2	37.2	33.3	31.4	23.5	21.6	19.6	
180	97	89.9	42.1	39.2	36.3	33.3	30.4	24.5	22.5	20.6	
190	100	87.2	41.2	38.2	35.3	32.3	29.4	24.5	22.5	20.6	
200	104	84.6	40.2	37.2	35.3	31.4	29.4	25.5	23.5	21.6	